


# CEWELD E 7024 (150)

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                         |                      |                    |                         |          |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|----------------------|--------------------|-------------------------|----------|
| TYPE                                        | High efficiency, rutile electrode with approximately 150% metal recovery                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                         |                      |                    |                         |          |
| APPLICATIONS                                | CEWELD® E 7024 (150) is a high performance electrode with a thick rutile coating and a recovery of 150%. For joining and surfacing in mechanical engineering, body and wagon building as well as in the fabrication of vessels and containers and in shipbuilding.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                         |                      |                    |                         |          |
| PROPERTIES                                  | CEWELD® E 7024 (150) has a high current carrying capacity and good striking properties. This electrode is very economical thanks to low spattering losses and easy slag removal.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                         |                      |                    |                         |          |
| CLASSIFICATION                              | AWS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | A 5.1: E 7024           |                      |                    |                         |          |
|                                             | EN ISO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2560-A: E 42 0 RR 73    |                      |                    |                         |          |
|                                             | F-nr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1                       |                      |                    |                         |          |
|                                             | FM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1                       |                      |                    |                         |          |
| SUITABLE FOR                                | <b>Rp&lt; 420 MPa (60ksi) ISO 15608: 1.1( ReH &lt; 275 MPa ), 1.2 (275 &lt; ReH &lt; 360 MPa), 1.3 (ReH &gt; 360 MPa &lt; 420 MPa)</b><br>1.0035, 1.0038, 1.0039, 1.0044, 1.0112, 1.0116, 1.0130, 1.0145, 1.0253, 1.0254, 1.0255, 1.0258, 1.0259, 1.0319, 1.0345, 1.0345, 1.0345, 1.0348, 1.0352, 1.0418, 1.0420, 1.0425, 1.0425, 1.0425, 1.0451, 1.0452, 1.0453, 1.0457, 1.0459, 1.0460, 1.0460, 1.0461, 1.0486, 1.0490, 1.0491, 1.0619, 1.1100, 1.0409, 1.0421, 1.0426, 1.0429, 1.0430, 1.0436, 1.0473, 1.0481, 1.0482, 1.0484, 1.0505, 1.0545, 1.0546, 1.0562, 1.0566, 1.0570, 1.0578, 1.0581, 1.0582, 1.8902, 1.8912, 1.8932<br>S235JR-S355JR, S235JO-S355JO, P195TR1-P265TR1, P195GH-P265GH, L245NB-L360NB, L245MB-L360MB, L415NB, L415MB, WStE 380, WStE 420, S420NL<br>A, B, D<br><b>ASTM A 106, Gr. A, B; A 283 Gr. A, C; A 285 Gr. A, B, C; A 501, Gr. B; A 573, Gr. 58, 65, 70; A 633, Gr. A, C; A 711 Gr. 1013; API 5 L Gr. B, X42, X52, X60</b> |                         |                      |                    |                         |          |
| APPROVALS                                   | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                         |                      |                    |                         |          |
| WELDING POSITIONS                           | <div>PA</div> <div>PB</div> <div>PC</div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                         |                      |                    |                         |          |
| TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%) | C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Si                      | Mn                   | P                  | S                       |          |
|                                             | 0.08                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0.3                     | 0.75                 | 0.025              | 0.025                   |          |
| MECHANICAL PROPERTIES                       | Heat Treatment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | R <sub>P0,2</sub> (MPa) | R <sub>m</sub> (MPa) | A <sub>5</sub> (%) | Impact Energy (J) ISO-V | Hardness |
|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                         |                      |                    | 0°C                     |          |
|                                             | As Welded                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 410                     | 550                  | 23                 | 60                      | HRc      |
| REDRYING                                    | 140°C / 2 hr                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                         |                      |                    |                         |          |
| CURRENT TYPE:                               | AC, DC+/-                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                         |                      |                    |                         |          |
| GAS ACC. EN ISO 14175                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                         |                      |                    |                         |          |



# CEWELD E 7024 (150)

E 7024 (150) 3,2 X 450MM

| Packaging | KG/unit | EanCode       |
|-----------|---------|---------------|
| Vacuum    | 2,6     | 8720682050736 |

E 7024 (150) 4,0 X 450MM

| Packaging | KG/unit | EanCode       |
|-----------|---------|---------------|
| Vacuum    | 2,7     | 8720682050743 |

E 7024 (150) 5,0 X 450MM

| Packaging | KG/unit | EanCode       |
|-----------|---------|---------------|
| Vacuum    | 2,6     | 8720682050750 |